


Extend the range of your DECT Phone Easy and Simple

- Up to 6 repeaters per base station
- Automatic handover of calls between cells
- 2 simultaneous calls per repeater
- Automatic registration method
- Supports W52P
- Additional coverage between base station and handset, up to 50m indoors and 300m outdoors



The Yealink DECT repeater can be deployed when there is a desire to extend the range of the W52P, The repeater can also be utilised wherever there is a need to increase limited coverage or improve reception in remote areas.



Normal Range



Extended Range

Up to 6 repeaters per base station

General features

- > Worldwide DECT support
- > Extending the DECT coverage
- > Supports automatic handover of calls between cells
- > Handling of 2 active calls simultaneously
- > Up to 6 repeaters per base station
- > Automatic registration method
- > Manual registration method

Frequency/Coverage

- > Frequency bands coverage:
DECT, EU/AU/NZ & US/CA
- > Additional coverage between base station and handset, up to 50m indoors and 300m outdoors
- > Receiver sensitivity: -92dBm
- > 2 internal omni-directional antennas

Design/Size

- > Indoor cabinet
- > Manual mounting kit
- > Easily mounted on walls
- > Size: 120(W) x 35(D) x 135(H)mm

Standards/Approvals

- > The DECT repeater is designed in accordance with the Digital Enhanced Cordless Telecommunications (DECT) standard
- > The DECT repeater is compliant with:
 - TBR6, TBR22 (Generic Access Profile, GAP)
 - ETS 300 700 - ETSI Wireless Relay Station Specification

Power supply

- > Input: 230 V/50-60HZ/45mA
- Output: 5V/300mA

LED Indicator

- > LED Indicator



*the repeater is perfect to use with the W52P